



Termomecanica

Pancake

Pol.	mm.	Comprimento (m)	Peso médio (kg)	*Pressão de Trabalho (PSi)
3/16" x 1/32"	4,76 x 0,79	15,0 - 15,3	1,30	2323
1/4 " x 1/32"	6,35 x 0,79	15,0 - 15,3	1,90	1677
5/16" x 1/32"	7,94 x 0,79	15,0 - 15,3	2,40	1312
3/8" x 1/32"	9,52 x 0,79	15,0 - 15,3	2,90	1079
1/2" x 1/32"	12,7 x 0,79	15,0 - 15,3	4,00	795
5/8" x 1/32"	15,87 x 0,79	15,0 - 15,3	5,10	629
3/4" x 1/32"	19,05 x 0,79	15,0 - 15,3	6,10	521
7/8" x 1/32"	22,22 x 0,79	15,0 - 15,3	7,20	444

Bobininhas

Pol.	mm.	Comprimento (m)	Peso médio (kg)	*Pressão de Trabalho (PSi)
3/16" x 1/32"	4,76 x 0,79	95,0 - 100,0	8,60	2323
1/4" x 1/32"	6,35 x 0,79	95,0 - 100,0	12,00	1677
5/16" x 1/32"	7,94 x 0,79	80,0 - 84,0	13,10	1312
3/8" x 1/32"	9,52 x 0,79	70,0 - 72,0	13,80	1079
1/2" x 1/32"	12,7 x 0,79	50,0 - 51,0	13,40	795
5/8" x 1/32"	15,87 x 0,79	45,0 - 45,6	15,20	629
3/4" x 1/32"	19,05 x 0,79	30,0 - 30,6	12,30	521

Recepção: (+55) (11) 4366-9777

Vendas: (+55) (11) 4366-9799 - vendas@termomecanica.com.br

Assistência técnica: (+55) 11 4366-9762 - engenharia@termomecanica.com.br



**O Cálculo da pressão foi estabelecido com coeficiente de segurança (adotado 5 conforme ABNT)*



Tubos em Barras (rígido) - com espessura 0,79mm

Pol.	mm.	Comprimento (m)	Peso médio (kg)	*Pressão de Trabalho (PSI)
3/8" x 1/32"	9,52 x 0,79	5,0	0,97	1314
1/2" x 1/32"	12,7 x 0,79	5,0	1,32	968
5/8" x 1/32"	15,87 x 0,79	5,0	1,67	766
3/4" x 1/32"	19,05 x 0,79	5,0	2,03	634
7/8" x 1/32"	22,22 x 0,79	5,0	2,38	541
1" x 1/32"	25,4 x 0,79	5,0	2,73	471
1 1/8" x 1/32"	28,57 x 0,79	5,0	3,08	418
1 1/4" x 1/32"	31,75 x 0,79	5,0	3,43	375
1 3/8" x 1/32"	34,92 x 0,79	5,0	3,79	341
1 1/2" x 1/32"	38,1 x 0,79	5,0	4,14	312
1 5/8" x 1/32"	41,27 x 0,79	5,0	4,49	287
1 3/4" x 1/32"	44,45 x 0,79	5,0	4,84	267
2" x 1/32"	50,8 x 0,79	5,0	5,55	233
2 1/8" x 1/32"	53,97 x 0,79	5,0	5,9	219

Tubos em Barras (rígido) - com espessura 1,58mm

Pol.	mm.	Comprimento (m)	Peso médio (kg)	*Pressão de Trabalho (PSI)
3/8" x 1/16"	9,52 x 1,58	5,0	1,76	2829
1/2" x 1/16"	12,7 x 1,58	5,0	2,47	2042
5/8" x 1/16"	15,87 x 1,58	5,0	3,17	1599
3/4" x 1/16"	19,05 x 1,58	5,0	3,88	1313
7/8" x 1/16"	22,22 x 1,58	5,0	4,58	1115
1" x 1/16"	25,4 x 1,58	5,0	5,29	968
1 1/8" x 1/16"	28,57 x 1,58	5,0	5,99	855
1 1/4" x 1/16"	31,75 x 1,58	5,0	6,69	766
1 3/8" x 1/16"	34,92 x 1,58	5,0	7,4	694
1 1/2" x 1/16"	38,1 x 1,58	5,0	8,1	634
1 5/8" x 1/16"	41,27 x 1,58	5,0	8,81	584
1 3/4" x 1/16"	44,45 x 1,58	5,0	9,51	541
2" x 1/16"	50,8 x 1,58	5,0	10,92	471
2 1/8" x 1/16"	53,97 x 1,58	5,0	11,62	443
2 1/2" x 1/16"	63,5 x 1,58	5,0	13,74	375
2 5/8" x 1/16"	66,67 x 1,58	5,0	14,44	357
3" x 1/16"	76,2 x 1,58	5,0	16,56	312
3 1/8" x 1/16"	79,37 x 1,58	5,0	17,26	299

*O Cálculo da pressão foi estabelecido com coeficiente de segurança (adotado 5 conforme ABNT)